

1" Rapid Z™-DRUM with Template Bearing INSTRUCTION MANUAL

DW1-CA & DW1-FA

INTRODUCION

Thank you for purchasing the NSI Solutions 1" Rapid Z™-DRUM with Template Bearing. The Rapid Z™-DRUM is a 1" vacuum brazed grinding drum designed to quickly grind and smooth stone and quartz. These drums are designed to be used in sequence after the Rapid Z™-CUT. The coarse grit drum will quickly clean up the rough surface left by the Rapid Z™-CUT. The fine grit drum will quickly smooth the surface left by the coarse grit drum so it is ready to polish. Please read these instructions thoroughly before using this tool. Keep these instructions in a place where operators can access it easily.



Scan QR Code to see resources and videos regarding the Rapid Z™ items or visit us at nsisolutions.com or YouTube channel **NSITools**.



Read and Understand All Instructions

Failure to follow all instructions listed below may result in electric shock, fire, and/or serious personal injury. Additionally, observe all safety instructions provided with the electric and air tools.



Use Proper Safety Gear

To prevent damage to eyes from flying debris, wear protective glasses or face shield. Be sure to wear waterproof safety boots, appropriate hearing protection and dust protection as required.



Inspect Before Use

Before each use, inspect the Rapid Z™-DRUM for damage. Never use a Rapid Z™-DRUM that has damaged components.



Wet Use Only

The Rapid Z™-DRUM is designed for wet use only.



Observe Maximum RPM

Maximum RPM 8,500



Caution

Always be sure that the grinder is switched off and unplugged from power (either electric or air) before installing/removing the Rapid Z™-DRUM or attempting to perform any inspection or maintenance.

INSTRUCTIONS

1. The Rapid Z™-DRUM is designed for clockwise rotation, looking down on the threaded arbor mounting hole, and should not be used on a grinder or tool with the opposite rotation.
2. The Rapid Z™-DRUM mounts to a male 5/8-11 thread (M14 thread on European version). Prior to use, ensure it is mounted tightly.
3. The Rapid Z™-DRUM is designed for wet use only. Use either center water feed or a sufficient external water spray. Ensure enough water is used to avoid creating dust.
4. Make sure the machine height is adjusted so that the bearing rides against the template and the drum is aligned with the stone to be ground.
5. With the Sink BULL™ or other grinding machine in place on the template, and the water running, start the motor. Work the drum around the template, grinding away stone, until the bearing contacts the template around the entire periphery. The coarse grit drum will grind away stone almost flush to the template leaving approximately .020" (.5mm) proud of the template.
6. After the coarse drum has been worked completely around the template switch to the fine grit drum and repeat the process. The fine drum will leave a surface flush to the template which is ready to polish.

CLEANING

The ball bearing template follower will last longer if it is blown dry, with compressed air, after each use.

All Rapid Z™ Products are Proudly Designed & Assembled in the U.S.A. from Global Components